

OVERVIEW

Terracoat InteriorTex is a range of ready-mixed textured coatings for interior use. They provide the unique combination of a quality architectural finish with outstanding economy through ease of application and a low material consumption rate. InteriorTex adheres to most interior surfaces including plywood, chipboard, anti-rust primed steel, gypsum dry wall, sand/cement render and concrete. InteriorTex is available in an attractive range of 50 colours

PRODUCT GRADES/CODES

G	62480
Smooth	62470
Superfine	62430
Normal	62410
Decor	62420
Granule	62490
Random	62440
Random Fine	62450
Suede	62515

PROPERTIES

InteriorTex is formulated from crushed and precisely graded fillers, acrylic binders. Its rich texture and in-built flexibility helps cover defects and minor cracks in the substrate. InteriorTex is available in a range of different texture grades and attractive colours.

InteriorTex G

InteriorTex G is a low build roller applied lightly grained textured coating. Consumption rates are low, making it a very economical finish.

Smooth

InteriorTex Smooth is a low build roller applied lightly textured coating. Consumption rates are low, making it a very economical finish.

Superfine

InteriorTex Superfine is a roller/spray applied texture which can be used in a wide range of finishes depending on the application method and material consumption. Finishes vary from fine spray to roller stucco.

Normal

InteriorTex Normal is a medium build textured finish applied by spray. A medium build spray pattern is the most popular finish.

Decor

InteriorTex Decor is a high build textured finish applied by decorative roller or hopper gun. The most popular finishes are roller stucco and coarse spray pattern.

Granule

InteriorTex Granule is a trowel applied texture giving a granular finish.

Random/Random Fine

InteriorTex Random is a trowel applied texture giving an alpine scratch finish. Random has excellent application characteristics, particularly on difficult substrates. It shows a lower density scratch pattern.

Suede

InteriorTex Suede is a medium build trowel applied finish. It is finished using a plastic trowel to give a suede effect finish.

AREA OF USE

InteriorTex is primarily designed for interior surfaces. InteriorTex can be used on surfaces of concrete, cement rendering, lightweight concrete, fair-faced block-work, plywood, anti-rust primed steel and galvanised steel. The coating performs equally well on gypsum dry-wall and chipboard and is widely used as a decorative ceiling and wall finish.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Terraco Acrylic Filler.

Old surfaces: Before applying InteriorTex to old surfaces, ensure the substrate is firm. First wash down the surface with a sugar soap solution, rinse and allow to dry before repairing or applying the primer.

PRIMING

Prime surfaces with a coat of Penetrating Primer prior to application of InteriorTex.

APPLICATION & CLEANING OF TOOLS

Spray application is done using a hopper gun and compressor, ensuring to mask off areas not requiring coating.

Roller application is done using a series of decorative rollers to achieve different patterns.

Trowel application is done using a steel trowel to lay on the material and a wetted plastic trowel is used to pattern the surface.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Interior Tex is supplied in 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

Grade	Specific Gravity	Viscosity ('000 cps.)	Material consumption (Kg / m ²)	Application method	Pack sizes (Kg.)
InteriorTex G	1.65	50-60	0,5-0,7	Roller	25
Smooth	1.65	50-60	0,6-0,9	Roller	25
Superfine	1.55	50-60	0,6-3,5	Spray, roller	25
Normal	1.60	50-60	1,5-2,0	Spray	25
Decor	1.60	55-65	2,5-3,5	Spray, roller	25
Granule	1.75	30-40	2,1-2,4	Trowel	25
Random	1.70	35-45	2,2-2,5	Trowel	25
Random Fine	1.70	35-45	2,1-2,4	Trowel	25
Suede	1.75	40-60	1,5-2,0	Trowel	25

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Granular textured coating.
Binder	Pure Acrylic.
Thinning	Water if required.
Drying Time	6-8 hours.
Toxicity	Non-toxic.
VOC Level	<5gm/ litre
Flame Spread	Class 0 ASTM E84-95b
Colours	50 standard colours.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

ROMANIA:

Terraco Romania SRL

Tel: +40 (0)749 203 133
Fax: +40 (0)318 148 810
E-mail: ahaque@terraco.com
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terraco.khn.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com