

OVERVIEW

Terraroc FC is a finish coat rendering compound designed for use to reface concrete after repair. It is used as the final coat in the Terraco concrete repair system but can also be used independently as a thin coat render on concrete up to 3mm. Terraroc FC is suitable for use over both interior and exterior concrete surfaces.

PROPERTIES

Terraroc FC is a blend of special cements, graded fillers, polymers and water retaining additives with the following properties:

- Ready to use
- Attractive smooth finish
- Excellent adhesion

AREAS OF USE

Terraroc FC is designed for use as a final coat in the Terraco concrete repair system in order to produce a smooth surface suitable for final decoration. It can also be used as a thin coat render for direct application on concrete for repairing fine cracks or surface defects.

PREPARATION OF SURFACE

When completing concrete repair work ensure that the surrounding concrete is free from oil, grease, dirt, surface contaminants and loose particles. Thoroughly soak complete substrate with water prior to application.

MIXING INSTRUCTIONS

Mix Terraroc FC with the recommended water with a mechanical mixer or hand held agitator for 3-5 minutes. Allow to stand for 5 minutes, restir and use (6.5 to 7.5ltr water/25kg Terraroc FC – depending on thickness of application).

APPLICATION & CLEANING OF TOOLS

Terraroc FC is applied by spray and levelled with a steel float. Smooth finishing is achieved with a wooden or foam float when Terraroc FC has set, moistening the float during use and brushing off loose particles with a soft brush afterwards.

Clean tools and equipment with water after use.

CURING

It is advisable to keep the surface moist during the first 48 hours to ensure proper curing.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terraroc FC is packed in 25kg valve craft bags.

Product should be stored in a clean, dry area, protected from direct sunlight and extreme heat and cold. Pallets may be stacked two high if care is taken. Opened sacks should be used first. Unopened sacks can be stored for 6 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Finish coat render for concrete repair system.
Binder	Hydraulic/organic.
Colours	Grey and white.
Set Time	1-2 hours.
Water Demand	26% to 30% (6.5 to 7.5ltr water/25kg Terraroc FC).
Application Thickness	0.5 - 3.0mm.
Yield	25kg powder + 7.5 ltr water gives 17.5 ltr of mix.
Consumption Rate	1.5kg/m ² /mm thickness
Packaging	25kg valve craft bags.
Storage	6 months in original unopened bag.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
 Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terraco.khn.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com