

OVERVIEW

Handycoat Fine is a ready to use filler and skim coat for most building surfaces, including sand / cement render and gypsum board. It has an extra fine particle size to give a high quality even surface for painting. Handycoat Fine is specially manufactured for the painter to repair and touch up interior surfaces, both old and new, prior to painting.

PROPERTIES

Handycoat Fine is made from a selected blend of acrylic polymers and precisely graded fillers. The product is:

- Easy to use.
- Does not flake off.
- Has high adhesion power.
- Has high coverage.
- Quick drying.
- Vapour permeable

AREAS OF USE

When dry, Handycoat Fine bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplasters, wood, galvanized steel lathings and all common building surfaces. Handycoat Fine is suitable for skimming over other Handycoat / Sprayplaster grades to produce an extra fine surface for fine finishing.

PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed away. Ridges and form oil must also be removed. The use of Penetrating Primer is recommended on dusting or flaking surfaces.

APPLICATION & CLEANING OF TOOLS

Apply the filler in a thin even layer. Apply two or more coats if necessary, allowing to dry between layers. Lightly sand down the final surface before painting, preferably within 24 hours of application.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handycoat Fine is supplied in 5kg, 25kg plastic pails and 25kg plastic bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Do not allow material to freeze. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Ready mixed quick drying filler for interior surfaces.
Binders	Acrylic copolymer.
Fillers	Fine precisely graded fillers.
Dilution	With water if required.
Coverage	0.2 -0.4kg/m ² depending on substrate conditions.
Layer Thickness	Maximum 1mm.
Specific Gravity	1.70 ± 0.05
Colour	White.
Durability	Negligible shrinkage.
Toxicity	Non-toxic.
Packaging	5kg and 25kg plastic pails, 25kg plastic bags.
Storage	12 month for plastic pails & 6 months for plastic bags - in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terraco.khv.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com