

OVERVIEW

Handycoat Washable is a ready- to-use filler and board jointing compound for most building surfaces, including sand/cement render and gypsum board. It gives a high quality, even surface for painting. Handycoat Washable is specially formulated for use in areas such as kitchens, bathrooms and hallways where painted surfaces may become damp and wet from time to time.

PROPERTIES

Handycoat Washable is made from a selected blend of acrylic polymers and precisely graded fillers. The product is:

- Easy to use
- Excellent adhesion
- Applicable up to 2mm in thickness
- High coverage
- Quick drying
- Vapour permeable
- Can be used in damp areas
- Washable

AREAS OF USE

When dry, Handycoat Washable bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplasters, wood, galvanised steel lathings and all common building surfaces. It is ideal for use as a gypsum board jointing compound and skimcoat. It is ideal in kitchens, bathrooms and hallways for patching hairline cracks in walls, ceilings, repair to damaged plaster/paint work, filling of defects, nail holes in woodwork, making good around door architraves and along the top of skirtings etc.

PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed away. Ridges and form oil must also be removed. The use of a Terraco Penetrating Primer is recommended on dusting or flaking surfaces.

APPLICATION & CLEANING OF TOOLS

Apply the filler in a thin even layer. If a thick coat is necessary, apply several thin layers, allowing to dry between layers. Lightly sand down the final surface before painting, preferably within 24 hour of application.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handycoat Washable is supplied in 5kg and 25kg plastic pails and 25kg plastic bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Water resistant filler for interior surfaces.
Binders	Styrene acrylate.
Fillers	Fine precisely graded fillers.
Dilution	With water if required.
Coverage	0.5 -1.5kg/m ² depending on substrate conditions.
Layer Thickness	Max 2mm.
Specific Gravity	1.65
Colour	White
Toxicity	Non-toxic.
Packaging	5 and 25kg plastic pails, 25kg plastic bags
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
 Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terraco.khn.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com