

#### OVERVIEW

Interior Tex Suede is a ready-mixed textured coatings for interior use. It produces an attractive Interior Tex Suede finish to any interior wall with outstanding economy through ease of application and a low material consumption rate. Interior Tex Suede adheres to most interior surfaces including plywood, chipboard, anti-rust primed steel, gypsum dry wall, sand/cement render and concrete. Interior Tex Suede is available in an attractive range of 50 colours.

#### PROPERTIES

Interior Tex Suede is formulated from crushed and precisely graded fillers, acrylic binders. Its rich texture and in-built flexibility helps cover defects and minor cracks in the substrate. Interior Tex Suede is available in a range of different texture grades and attractive colours. Interior Tex Suede is a medium build trowel applied finish. It is finished using a plastic trowel to give a Interior Tex Suede effect finish.

#### AREA OF USE

Interior Tex Suede is primarily designed for interior surfaces. Interior Tex Suede can be used on surfaces of concrete, cement rendering, lightweight concrete, fairfaced stonework, brickwork, blockwork, plywood, anti-rust primed steel and galvanised steel.

The coating performs equally well on gypsum dry wall and chipboard and is widely used as a decorative ceiling and wall finish.

#### PREPARATION OF SURFACE

**New surfaces:** Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with an appropriate filler.

**Old surfaces:** Before applying Interior Tex Suede to old surfaces, ensure the substrate is firm. First wash down the surface with a soda/water solution, rinse and allow to dry before repairing or applying the first coat.

#### PRIMING

Prime surfaces with a coat of Penetrating Primer prior to application of Interior Tex Suede.

#### APPLICATION & CLEANING OF TOOLS

Trowel application is done using a steel trowel to lay on the material and a wetted plastic trowel is used to pattern the surface.

Clean tools and equipment with water after use.

#### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

#### PACKAGING & STORAGE

Interior Tex Suede is supplied in 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

#### TECHNICAL DATA

<b>Product</b>	Acrylic based textured coating.
<b>Binder</b>	Styrene acrylate.
<b>Thinning</b>	Water if required.
<b>Drying Time</b>	3 - 4 hours.
<b>Specific Gravity</b>	1.75
<b>Viscosity</b>	40,000 – 60,000 cps
<b>Material Consumption</b>	1.5-2.0 kg/m <sup>2</sup>
<b>Application Method</b>	Trowel
<b>Toxicity</b>	Non-toxic
<b>Flame Spread</b>	Class 0 ASTM E84-81H
<b>Colours</b>	50 standard colours.
<b>Packaging</b>	25kg plastic pails
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

#### CHINA:

Terraco Architectural Coatings China Co., Ltd.  
Tel: +86 (0)20 8759 4742  
Fax: +86 (0)20 8526 8056  
E-mail: sales@terraco.com.cn  
Web: www.terraco.com.cn

#### Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18  
Fax: +86 (0)21 625205 47  
Email: sales@terraco.com.cn  
Web: www.terraco.com.cn

#### EGYPT:

#### Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58  
Fax: +20 (0)22 29184 80  
E-mail: terraco@terraco.com.eg  
Web: www.terraco.com.eg

#### JORDAN:

#### Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751  
Fax: +962 (0)6 553 6560  
E-mail: terraco@nol.com.jo  
Web: www.terraco.jo

#### IRELAND:

#### Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555  
Fax: +353 (0) 404 66654  
E-mail: technical-centre@terraco.com  
Web: www.terraco.com

#### PAKISTAN:

#### Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8  
Fax: +92 (0)42 3529 70 55  
Email: terraco@terraco.pk  
Web: www.terraco.com

#### ROMANIA:

#### Terraco Romania SRL

Tel: +40 (0)749 203 133  
Fax: +40 (0)318 148 810  
E-mail: ahaque@terraco.com  
Web: www.terraco.com

#### RUSSIA:

#### OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237  
Fax: +7 (0)495 6273 881  
E-mail: adm@terraco.ru  
Web: www.terraco.ru

#### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
Fax: +7 (0)4212 410591  
E-mail: terracovostok@terraco.khn.ru  
Web: www.terraco.com

#### SOUTH KOREA:

#### Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551  
Fax: +82 (0)2 5671 771  
E-mail: terraco@terraco.co.kr  
Web: www.terraco.co.kr

#### THAILAND:

#### Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58  
Fax: +66 (0)2 946 68 59  
E-mail: terraco@terraco.co.th  
Web: www.terraco.com

#### TURKEY:

#### Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423  
Fax: +90 (0)222 236 0425  
E-mail: terraco@terraco.com.tr  
Web: www.terraco.com.tr

#### UAE:

#### Terraco UAE Ltd

Tel: +971 (0)4 326 2699  
Fax: +971 (0)4 326 2733  
E-mail: terraco@terraco.ae  
Web: www.terraco.com

#### UK:

#### ADDAGRIP

Tel: +44 (0)1825 761 333  
Fax: +44 (0)1825 768 566  
E-mail: sales@addagrip.co.uk  
Web: www.addagrip.co.uk / www.terraco.com

#### VIETNAM:

#### Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100  
Fax: +84 (0)650 3 820 101  
E-mail: terraco@terraco.com.vn  
Web: www.terraco.com