

OVERVIEW

Handytex is an acrylic based ready mixed texturing compound for use on all types of interior ceiling and walls. Handytex is a versatile product that can be applied with a selection of application tools and rollers to give a wide range of attractive textures and finishes. Handytex gives surfaces a white attractive finish that covers hairline cracks and minor blemishes. Handytex is easy to apply and allows the user to create innovative patterns and effects. Handytex can be tinted using conventional universal colourant pastes.

PROPERTIES

Handytex is a selected blend of acrylic polymers, pigments, graded fillers and other additives. The product is:

- Easy to use
- Acrylic based
- Non combustible
- Versatile - wide range of possible textures and finishes

AREAS OF USE

Can be used on most interior ceiling and wall substrates including pre-cast concrete, sand cement render, gypsum plaster and dry-wall.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Terraco Handycoat Exterior.

Old surfaces: Before applying InteriorTex to old surfaces, ensure the substrate is firm. First wash down the surface with a sugar soap solution, rinse and allow to dry before repairing or applying the primer

PRIMING

Prime surfaces with a coat of Penetrating Primer prior to application of Handytex.

APPLICATION & CLEANING OF TOOLS

Stir well before use. Handytex may be diluted with up to 10% water for light textures. Practice texturing on a board before starting work until desired effect is achieved. Apply a liberal coat over 1m² at a time using the application brush or roller. Use one of the texturing tools to achieve the desired pattern before moving on. Work in this way until the ceiling or wall is completed, at all times maintaining a wet edge between textured areas. Finish the edge between ceiling and wall with a small paint brush to produce a smooth border approx. 15-30mm wide. Allow to dry 12-24 hours. Handytex can be top-coated with one of the Terraco decorative topcoats such as Ecotop, Ecotex, Fresco or Handyplus. Do not apply Handytex at temperatures below 5°C.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handytex is supplied in 5kg and 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Acrylic based texturing compound.
Binder	Acrylic
Thinning	Water if required.
Drying Time	3 - 4 hours.
Specific Gravity	1.70
Coverage	0.6-1.2 kg/m ²
Application Method	Brush/roller/comb
Flame Spread	Class 0
Colour	White
Packaging	25kg plastic pails.
Storage	12 months in original unopened containers.

PATTERN TYPE - Application Method

Scroll	Apply a liberal coat by roller. Pattern the surface using the STIPPLING PAD by placing the pad onto the surface of the freshly applied material and move it around in a series of figure of eight movements.
Broken Leather	Apply as above. Pattern the surface using the STIPPLING PAD covered in polythene by spinning the brush in opposite directions while moving across the coated surface without moving the brush away.
Bark Effect	Apply as above. Pattern surface using the BARK EFFECT ROLLER
Diagonal Effect	Apply as above. Pattern surface using the DIAGONAL EFFECT ROLLER
Diamond Effect	Apply as above. Pattern surface using the DIAMOND EFFECT ROLLER
Diagonal Knockdown	Apply as above. Pattern surface using the DIAGONAL EFFECT ROLLER. Using knockdown tool.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:
Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:
Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:
Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:
Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:
Terraco Romania SRL

Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:
OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terraco.khn.ru
 Web: www.terraco.com

SOUTH KOREA:
Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:
Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:
Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:
Terraco UAE Ltd

Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:
ADDAGRIP

Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:
Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com