

OVERVIEW

Terragrout is a hard-wearing, water-resistant grout for filling joints in exterior and interior walls and floor tiles, mosaics and clinkers. It is specially formulated to fill joints of up to 5mm in width. It is easily applied by hand and because of its unique composition, does not shrink when dry. Terragrout is manufactured in 10 standard colours.

PROPERTIES

Terragrout is composed of precisely graded, marble powder, a blend of special cements, water-repellent materials, oxide colours, plasticizers and polymers. Terragrout does not curl up during application and gives a water- and weather-resistant joint with no shrinkage cracks. All colours are light and lime fast.

AREAS OF USE

Terragrout can be used on materials such as wall and floor tiles, clinkers and mosaics, where joints do not exceed 5mm in width.

PREPARATION OF SURFACE

Ensure that all tile joints and edges are free and clean of excess tile fixing mortar and foreign matter.

MIXING

Thoroughly mix Terragrout at the ratio of approximately 1ltr water to 4kg. Terragrout powder. Allow to stand for 15 minutes. Mix again. Terragrout is then ready for use.

APPLICATION & CLEANING OF TOOLS

Wait until the Terrafix has set (approx. 24 hours) before grouting. Apply Terragrout diagonally into the joints with a rubber edged spatula. Remove excess grout with a moist sponge before drying. Do not apply Terragrout to an area which is so large that it cannot be completed within an hour. Porous tiles should be moistened with water before grouting. After Terragrout has dried and before it has hardened, polish the tiles with a clean, dry cloth leaving the joints flush with the tile. 24 hours after grouting, moisten the joints with a wet sponge.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terragrout is supplied powder form in 5kg and 20kg valve bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 6 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Tile grouting compound for joints up to 5mm.
Binders	Hydraulic/latex.
Filler	Crushed, precisely graded extenders.
Colours	Available in 10 standard colours.
Pigments	Fast to light, lime, salt and cement.
Material Consumption	0.5 - 1.0kg per m ² depending upon width of tile joints.
Water Consumption	Approximately 1ltr clean water to 4kg Terragrout powder.
Packaging	Supplied in powder form in 5kg and 20kg valve bags.
Storage	6 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

ROMANIA:

Terraco Romania SRL

Tel: +40 (0)749 203 133
Fax: +40 (0)318 148 810
E-mail: ahaque@terraco.com
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terraco.khn.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com